


The scalable compact rack server

EXPRESS5800/R120b-2

ENERGY EFFICIENT SERVER FOR THE MOST DEMANDING APPLICATIONS



HIGH PERFORMANCE

FLEXIBLE SCALABILITY

SIMPLIFIED MANAGEABILITY

Scalable and green

The EXPRESS5800/R120b-2 is a dual-socket 2U rack server enabling high-density mounting and combining outstanding performance, reliability, energy saving parts and green technology. In addition, the platform features internal scalability and large memory capacity for future growth.

For compute intensive environments

Perfect for virtualization solutions, database servers, consolidation of business-critical applications, Web servers which all process high volumes of data in the background of their primary tasks.

Advanced system management

R120b-2 comes standard with a practical remote management solution. Remote monitoring and management are possible through a Web browser regardless of the status of the operating system and even when the platform is turned off.

High performance

- Powered by Intel® Xeon® 5600 series processors
- Up to 192GB DDR3L-1333 memory

Flexible scalability

- Up to four PCI Express 2.0 and one PCI Express support
- Supports up to twelve 2.5-inch SAS drives or six 3.5-inch SATA drives
- Optional 3.5-inch bay to mount a storage backup device

Simplified manageability

- The EXPRESSBUILDER setup support tool provides step-by-step guidance via intuitive GUI and automates the setup process to reduce hands-on management.
- The ESMPRO management software and the EXPRESSSCOPE Engine 2 remote management controller interact to monitor, control and troubleshoot from a remote console.

HARDWARE SPECIFICATION

MODEL	EXPRESS5800/R120b-2
Processors	Number of processor: 1-2 Intel® Xeon® Processor X5690 (3.46GHz/6C/12MB)* Intel® Xeon® Processor X5687 (3.60GHz/4C/12MB)* Intel® Xeon® Processor X5675 (3.06GHz/6C/12MB)* Intel® Xeon® Processor X5650 (2.66GHz/6C/12MB) Intel® Xeon® Processor E5645 (2.40GHz/6C/12MB)* Intel® Xeon® Processor E5620 (2.40GHz/4C/12MB) Intel® Xeon® Processor E5606 (2.13GHz/4C/8MB) Intel® Xeon® Processor E5503 (2GHz/2C/4MB)* *2.5-inch disk drive model only
Memory	DDR3-1333 ECC registered low power DIMM (1/2/4/8GB), DDR3-1066 ECC registered low power DIMM (16GB) Max.: 192GB (12 x 16GB)
Maximum storage	3.5-inch SATA: 12TB (6 x 2TB) 2.5-inch SAS: 10.8TB (12 x 900GB), 2.5-inch SATA: 12TB (12 x 1TB), 2.5-inch SSD: 1.2TB (12 x 100GB)
Removable media	1 bay for optical disk drive 1 bay for internal tape drive
Expansion slots	Total: 5 slots available*, ** 1 x PCIe 2.0 x8 (x16 connector) 2 x PCIe 2.0 x8 (x8 connector) 1 x PCIe 2.0 x4 (x8 connector) 1 x PCIe x4 (x8 connector) * The slot mix changes by installing optional riser cards ** Plus one dedicated slot for a RAID controller
Video	Integrated in the Server Management Controller (32MB)
Network	2 x 1000BASE-T/100BASE-TX/10BASE-T + 1 x 100BASE-TX for management
Power consumption	810VA/800W (max., at 100V)
Redundant power supply	Optional, hot plug
Redundant cooling fan	Optional, hot plug
Management	Server Management Controller (EXPRESSSCOPE Engine 2)
Interface	2 x VGA, 1 x keyboard, 1 x mouse, 1 x serial*, 4 x USB 2.0 (plus 4 x internal USB 2.0), 2 x LAN, 1 x management LAN * Total 2 with optional port
Dimensions (W x D x H) and weight	445.2 x 721.2 x 86.7 mm / 17.5 x 28.4 x 3.4 in (2U) Max.: 31kg / 68.34lb
Temperature and humidity conditions	Operating: 10 to 35 °C / 20 to 80% (non-condensing) Non-operating: -10 to 50°C / 20 to 80% (non-condensing)
Operating systems and virtualization software	Microsoft® Windows Server® 2003 R2, Standard Edition / Enterprise Edition Microsoft® Windows Server® 2003 R2, Standard x64 Edition / Enterprise x64 Edition Microsoft® Windows Server® 2008 Standard / Enterprise Microsoft® Windows Server® 2008 Standard (x64) / Enterprise (x64) Microsoft® Windows Server® 2008 R2 Standard / Enterprise Red Hat® Enterprise Linux® VMware® ESX™i 4.1

Note : For Linux support, go to the NEC website at www.nec.com/express, or contact your local NEC sales office

©Copyright 2011 NEC Corporation. The information and specification contained in this publication are subject to modification without prior notice. Microsoft and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel, Intel Logo, Pentium, Pentium Inside, Xeon, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Linux is a trademark of Linus Torvalds. Red Hat is a registered trademark of Red Hat, Inc. in the U.S. VMware is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions. All other names of products and brands cited are the property of their respective owners. NEC declines all responsibility in the case of photographic or typing errors.



Asia (APAC)
NEC Corporation

7-1, Shiba 5-chome Minato-ku
Tokyo 108-8001 Japan

www.nec.com/express

Europe (EMEA)
NEC France
IT Platform Solutions Division

10, rue Godefroy
92821 Puteaux Cedex France
+33 1 42 91 80 00

www.nec-itplatform.com

North America
NEC Corporation of America
Information Technology Group

2880 Scott Blvd.
Santa Clara, CA 95050 U.S.
+1 866 632 3226

www.necam.com/servers